



**KEY**

**DETAIL C2**  
 750mm traffic cones on AP singles (50mph or more) and AP duals 50 or 60mph.

**DETAIL B**  
 Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.  
 Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

**SAFETY ZONE DIMENSIONS**  
 Permanent speed limit 40mph  
 Sideways safety zone 0.5m  
 Longways safety zone 15m  
 (Dimensions are minima)

**Notes:**  
 1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).  
 2) 45° tapers have 1.2m spacing, no relaxations.  
 3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

**Legend:**  
 Traffic sign  
 Traffic cone  
 Road closed  
 Diversion Route

Qty: 2 Ref: 2702 End of temporary diversion route	
Qty: 3 Ref: 2702 Start of temporary diversion route	
Qty: 2 Ref: 2702 Start of temporary diversion route	
Qty: 8 Ref: 2703 Direction of temporary diversion route from junction ahead	
Qty: 6 Ref: 2703 Direction of temporary diversion route from junction ahead	
Qty: 6 Ref: 2703 Direction of temporary diversion route from junction ahead	
Qty: 1 Ref: 573 Direction to hazard left	
Qty: 1 Ref: 573 Direction to hazard right	
Qty: 2 Ref: 7010-FP-13-9 Nature of temporary hazard ahead - Road Closed	
Qty: 3 Ref: 7010-FP-13-9 Nature of temporary hazard ahead - Road Ahead Closed	
Qty: 2 Ref: 7010.1 Nature of temporary hazard ahead - Road Ahead Closed	

<b>Designer</b>	
Drawn by	JH
Date	10/01/25
CHK BY	CS

Chipping Sodbury  
 Wickwar Road, BS37 6GA  
 ///horses.avocado.sandpaper

**TEMPORARY  
 TRAFFIC MANAGEMENT  
 Road Closure**



Drawing No  
**HSW-SCTM6517-01**  
 Original drawing size A0 - NTS

**Location 1 – 5x Night**