



KEY

DETAIL C2

750mm traffic cones on AP singles (50mph or more) and AP duals 50 or 60mph.

Notes:
1) During darkness, warning 55 lamps are to be provided at 5m centres.

DETAIL B

Single/Dual carriageway 40mph or less - 450mm traffic cones, spacing 1.5m.
Dual carriageway national speed limit - 750mm traffic cones, spacing 1.5m, relaxation 3m.

Notes:
1) During darkness, warning lights to BS EN 12352:2006 should be provided in accordance with Table A1.3 (Appendix 1).
2) 45° tapers have 1.2m spacing, no relaxations.
3) On motorways and NSL AP duals with hard shoulders, 1m cones will be required for both standard and relaxation works for lead tapers and the facing wall of lane changes.

Traffic sign
Traffic cone
Road closed
Diversion Route

SAFETY ZONE DIMENSIONS
Permanent speed limit 40mph
Sideways safety zone 0.5m
Longways safety zone 15m
(Dimensions are minima)

Qty: 2 Ref: 2702 End of temporary diversion route	
Qty: 1 Ref: 2702 Start of temporary diversion route	
Qty: 3 Ref: 2702 Start of temporary diversion route	
Qty: 4 Ref: 2703 Direction of temporary diversion route from junction ahead	
Qty: 3 Ref: 2703 Direction of temporary diversion route from junction ahead	
Qty: 2 Ref: 2703 Direction of temporary diversion route from junction ahead	
Qty: 1 Ref: 2706 Roundabout ahead leading to temporary diversion route	
Qty: 1 Ref: 2706 Roundabout ahead leading to temporary diversion route	
Qty: 1 Ref: 573 Direction to hazard right	
Qty: 3 Ref: 7010-FP-13-9 Nature of temporary hazard ahead - Road Ahead Closed	
Qty: 2 Ref: 7010-FP-13-9 Nature of temporary hazard ahead - Road Closed	
Qty: 1 Ref: 7010.1 Nature of temporary hazard ahead - Road Ahead Closed	

Designer	
Drawn by	JH
Date	10/01/25
CHK BY	CS

Chipping Sodbury
Wickwar Road, BS37 6GA
///printout.glowe.repaid

TEMPORARY
TRAFFIC MANAGEMENT
Road Closure



Drawing No
HSW-SCTM6517
Original drawing size A0 - NTS

Location 2 – 3 consecutive Sundays